



KLINGER SHIELD INSULATION SETS



Insulation sets are used to limit corrosion in pipeline systems. Where dissimilar metals are present, the sets remove the possibility of the system acting as a galvanic cell and reduce the risk of galvanic corrosion of the pipework.

Insulation sets are also used to isolate cathodically protected piping systems where they prevent the flow of electro-static charge.

Each insulation set comes with a KLINGER Shield insulation gasket, insulating washer set, high temperature insulation sleeves.



Figure 1 – Typical assembly with GW1 washers

Klinger Shield uses Thermica facing which is a CNAF fibre; using mica and NBR binder offers high flexibility, high temperature resistance and excellent compatibility across a broad range of chemicals.

COMPONENT	UNITS	KLINGER THERMICA	MICA SLEEVES
Compressibility	%	12	N/A
Recovery	%	<55	N/A
Stress Relaxation (DIN 52913, 50MPa, 16h. 300°C)	MPa	28	N/A
Density	g/cm ³	1.7	1.8
Dielectric Strength	kV/mm	15	22
Temperature Range	°C	-200 to 350	-100 to 700

GENERAL PROPERTIES

- » Continuous service up to 350°C
- » Suitable for RTJ, RF and mismatched RF to RTJ flanges
- » Suitable for pressure ratings from Class 150 to 2500
- » Compressed fibre facings of mica & synthetic fibres bound with NBR on a high strength metallic core
- » Excellent chemical resistance
- » 3xA anti-stick finish

TESTS & CERTIFICATIONS FOR KLINGER SHIELD

- » Fire-safe to DIN EN ISO 10497 / API 607
- » Fire-safe to API 6FB
- » Thermica complies with BS 7531 Grade AX

KLINGER SHIELD INSULATION SET COMPONENTS

Insulating Gasket:	Class 150 to 2500	4.6mm Thermica with metallic core
Insulating Washers:	Class 150 to 2500:	3.2mm HCS Washers 4 washers per bolt, suitable for use up to 260°C
Insulating Sleeves:	Mica, wall thickness 0.75mm, 1 per bolt	




Figure 2 – Shield HT Insulation sets can be used between raised face & RTJ flanges and mismatched combinations. Washers shown are HCS type.

HEAD OFFICE

KLINGER Ltd
Wharfedale Road
Euroway Trading Estate
Bradford BD4 6SG

Tel: 01274 688 222
Fax: 01274 688 549
www.klinger.co.uk
enquiries@klingeruk.co.uk

KLINGER RUNCORN

Tel: 01928 577 030
Fax: 01928 575 233

KLINGER SOUTHAMPTON

Tel: 02380 611 855
Fax: 02380 610 360

KLINGER ABERDEEN

Tel: 01224 772 962
Fax: 01224 772 953

KLINGER IMMINGHAM

Tel: 01469 575 289
Fax: 08449 676 779

KLINGER MIDDLESBROUGH

Tel: 01642 220 289
Fax: 01642 220 290

KLINGER GRANGEMOUTH

Tel: 01324 472 231
Fax: 01324 482 111



FM 602916

FM 10571

OHS 570166

EMS 570165